

Specifications:

- **Model Number** - AID-QV922R
- **Image device** - 1/3" Sony New Structure Super HAD Color CCD
- **Image Processor** - DSP (Digital Signal Processor)
- **Effective Pixels** - 768(H) x 494(V)
- **TV system** - NTSC, 525lines / 2:1interlace
- **Scan freq.** - N / A
- **Synchronization** - Internal
- **H. Resolution** - 550TVL
- **Sensitivity** - 0.02 Lux(F1.2@40IRE), 0 Lux with built-in 35 infrared LEDs
- **S/N Ratio** - More than 50dB with AGC OFF at 50IRE
- **Electronic Iris** - 1/60~1/100,000sec
- **White Balance** - 2000~8000K Automatic tracking
- **WDR Mode** - N / A
- **Digital Slow Shutter** - N / A
- **BLC** - Built-in, Center weighted
- **BLC Zone** - N / A
- **AGC** - 28dB Max
- **Dip Switches** - ELC/ALC, BLC, AGC, Flickerless, Sharpness, Day/Night
- **Potentiometer** - Video level adjustment(Iris)
- **V. Phase adjustment range** - N / A
- **V. phase locking range** - N / A
- **Video Output** - VBS 1Vpp +/-10%, 75ohm
- **Built-in Lens** - f=9~22mm F1.4/F1.4~F360 DC drive auto iris IR corrected, switched IR cut filter D/N lens
- **Infrared LEDs** - 35pcs @ 850nm
- **Indoor Night Observation Distance** - 20 Meters or 21.9 Yards(66ft) at 40IRE of video output level
- **Operating Power** - 24VAC(12~28.8VAC) or 12VDC (10.5~30VDC), 10Watts max
- **Operating condition** - -10°C~+50°C or 14°F~+122°F 85% RH. Max. non-condensing
- **Dimension** - 100(Pi) x 102(H) mm or 3 15/16(Pi) x 4 (H) inches
- **Weight** - approximately 350g or 12.34oz